ICATCH-DM524211-L

戶外半球5MP攝像機





主要特點

- -
- -



unit: mm

iCATCH

ONVIF MADE IN TAIWAN FC CE RoHS

ICATCH-DM524211-L

型號		ICATCH-DM524211-L
產品圖片		
攝影機	攝像元件	1 / 2.8 " CMOS
	圖像像素	2592 x 1944
	電子快門	1 / 4 s ~ 1 / 10,000 s
	最低照度	0 lux with illuminate on
	鏡頭	3.6mm
	可視角度	水平視角：97°±5° 垂直視角：72°±5°
	白光投射距離	30M IR
	寬動態	>100 dB
	信噪比	-
	數位降噪	3D DNR
影像	影像壓縮格式	主碼流：H265/H264/MJPEG 子碼流：H265/H264/MJPEG
	H.264編碼標準	Baseline Profile / Main Profile / High Profile
	解析度	5MP(2952x1944), 2K(2560x1440), 1080P(1920x1080), 720P(1280x720)
	第一碼流 (S1)	5MP/2K/FHD/HD (60Hz:1~30fps ; 50Hz:1~25fps)
	第二碼流 (S2)	HD/SD/nHD (60Hz:1~30fps ; 50Hz:1~25fps)
	碼流 (BitRate)	32 Kbps ~ 16 Mbps
	串流形式	VBR / CBR
	影像設置	感興趣區域、飽和度、亮度、色調、對比、寬動態、銳利度、鏡像、翻轉等
	ROI	支援
聲音	音頻格式	G.711 A/U, PCM
	聲音輸入	1 CH 內建麥克風
	聲音輸出	1 CH 內建喇叭
介面	網路接口	RJ45
	警報輸入	0
	警報輸出	0
	儲存	micro SD 卡
	重置	支援
功能	遠端監控	瀏覽器 / NVR / NVMS2.0
	Web瀏覽器	Chrome70+,Firefox 30.0-51,Safari 8.0-11, Edge
	通信協議	TCP/IP,HTTP,HTTPS,FTP,DHCP, DDNS,RTP,RTSP,RTMP
	接口協議	ONVIF S/T/G
	智能警報	-
	一般功能	浮水印、影像遮罩、設備狀態偵測
	安全	韌體加密，HTTPS, IP 地址過濾, 非法登入 802.1x , HTTP/RTSP 的 Basic 與 Digest 驗證
	PoE 供電	PoE Class 0/3(IEEE802.3af)
其他	電源	DC 12V / PoE
	消耗功率	< 8W
	工作環境	-30°C to 60°C
	尺寸	122*122*98mm
	重量	Approx. 550g
	防水等級	IP67

*如有更改恕不另行通知

202603

ICATCH-DM524211-L

5MP Outdoor Dome Fix Camera





Main Features

- -
- -



unit: mm

iCATCH

ICATCH-DM524211-L

Model		ICATCH-DM524211-L
Picture		
Camera	Image Sensor	1 / 2.8 " CMOS
	Effective Pixels	2592 x 1944
	Electronic Shutter	1 / 4 s ~ 1 / 10,000 s
	Minimum Illumination	0 lux with illuminate on
	Lens	3.6mm
	Viewing Angle	Horizontal: 97°±5° Vertical: 72°±5°
	White Light Distance	30M IR
	Wide Dynamic Range (WDR)	>100 dB
	Signal-to-Noise Ratio (S/N Ratio)	-
	Digital Noise Reduction (DNR)	3D DNR
Video	Video Compression	Main stream: H.265 / H.264 / MJPEG Sub stream: H.265 / H.264 / MJPEG
	H.264 Encoding Standard	Baseline Profile / Main Profile / High Profile
	Resolution	5MP(2952x1944), 2K(2560x1440), 1080P(1920x1080), 720P(1280x720)
	Main Stream (S1)	5MP/2K/FHD/HD (60Hz:1~30fps ; 50Hz:1~25fps)
	Sub Stream (S2)	HD/SD/nHD (60Hz:1~30fps ; 50Hz:1~25fps)
	BitRate	32 Kbps ~ 16 Mbps
	Stream Type	VBR / CBR
	Image Settings	Region of interest (ROI), saturation, brightness, hue, contrast, wide dynamic range (WDR), sharpness, mirroring, flipping, etc.
	ROI (Region of Interest)	Support
Audio	Audio Compression Format	G.711 A/U, PCM
	Audio Input	1 CH Built-in microphone
	Audio Output	1 CH Built-in speaker
Interface	Network Interface	RJ45
	Alarm Input	0
	Alarm Output	0
	Storage	micro SD card
	Reset	Support
Functions	Remote Monitoring	Browser / NVR / NVMS2.0
	Web Browser	Chrome70+,Firefox 30.0-51,Safari 8.0-11, Edge
	Communication Protocol	TCP/IP,HTTP,HTTPS,FTP,DHCP, DDNS,RTP,RTSP,RTMP
	Interface Protocol	ONVIF S/T/G
	Smart Alarm	-
	General Functions	Watermark, image masking, device status detection
	Security	Firmware encryption, HTTPS, IP address filtering, unauthorized login detection, 802.1X, Basic and Digest authentication for HTTP/RTSP
	PoE Power Supply	PoE Class 0/3(IEEE802.3af)
Others	Power Supply	DC 12V / PoE
	Power Consumption	< 8W
	Operating Environment	-30°C to 60°C
	Dimensions	122*122*98mm
	Weight	Approx. 550g
	Ingress Protection Rating	IP67

*Subject to change without notice

202603